

VESTWOODS

SMART RESIDENTIAL ESS SOLUTION

VE51200W




Most safety LiFePO₄
as cathode material



Long cyclic life-6000
cycles (80%DOD)




Max. current
150A



IP65 for outdoor
installation

SPECIFICATION

Model	VE51200W
Schematic Diagram	
Cell Type	LFP
Nominal Energy	10.24kWh
Nominal Capacity	200Ah
Nominal Voltage	51.2V
Operating Voltage Range	42.0 ~ 57.6V
Nominal Charge Voltage	57.6V
Charge Current/Max. Continuous	150A
Discharge Cut-off Voltage	42.0V
Discharge Current/Max. Continuous	150A
Recommended Depth of Discharge	80%
Ambient Temperature/Charge	0~60°C
Ambient Temperature/Discharge	-20~60°C
Dimension(W*H*D)	530*762*260.5mm(With Battery Bracket)
Weight	Approx. 91.0kg (With Battery Bracket)
IP Rating	IP65
Expansion	Max. 15 Units in Parallel
Color	White
Communication	CAN/RS485/WIFI/Bluetooth
Cooling Mode	Natural Cooling
Cycle Life	6000 Cycles, 80%DOD@25°C
Design Life	15+ Years (25°C)
Installation Method	Floor Mounted
Allowed Humidity Range	≤95% RH
Altitude	<2000m
Protections	Over Charge/Over Discharge/Over Temperature/Over Current/Short Circuit etc.
Compatible Inverters	Deye/Solis/Hoymiles/Senergy/Afore/Megarevo/SRNE/Inhenergy etc.
Design Standards	UN38.3/ IEC62619/CE-EMC/IEC RED

Disclaimer:

This document may contain forecast information, including but not limited to future finances, operations, product series, new technologies, etc. Due to practice the uncertainty in the actual results may differ from the predicted information. Therefore, the information in this document is for reference only and does not constitute any offer or promise. Vestwoods may modify the above information without notice.

